

MULTIPLE LINE GREASE PUMPS

FB SERIES

Number of outlets : 1 – 24
Maximum counterpressure : 350 bar
Motor power : 0.37 Kw
Tank capacity : 10-20-30 Kg.

External transmission ratio	Internal transmission ratio	Overall transmission ratio	Motor rotation speed (rpm)	Control shaft rpm	Maximum flow rate for each outlet with electric motor 1500 rpm (cm ³ /min)
10:1	6.6:1	66:1	1500	22.7	0 – 3.40
7.5:1	6.6:1	49.5:1	1500	30.3	0 – 4.50

- Adjustable flow rate at each outlet (from zero to maximum value).
- Outlet fitting with union (pipe Ø 8)
- Electric minimum level gauge (optional on 10 and 30 Kg versions/ not available on 20 kg version).

Ordering numbers

FB 20⁽¹⁾	/	20⁽²⁾	/	10⁽³⁾	C⁽⁴⁾	/380 V⁽⁵⁾ 50 Hz
----------------------------	----------	-------------------------	----------	-------------------------	------------------------	-----------------------------------

(1) TANK CAPACITY : **10-20-30 kg**
(2) NUMBER OF OUTLETS :
(3) EXTERNAL TRANSMISSION RATIO :
(4) GAUGE : **C = WITH S = WITHOUT**
(5) POWER SUPPLY VOLTAGE :

PUMP CHARACTERISTICS

FB10

