

Kit portatile per travaso gasolio con elettropompa a 12 o 24 volt a corrente continua. Trova impiego in tutti quei casi in cui è richiesta l'erogazione o il travaso di gasolio avendo solamente un'alimentazione elettrica da batteria.

Portable kit for diesel fuel transferring with 12V or 24V DC electric pump. It is useful when the distribution or the transferring of diesel fuel are required, but when only the electric power supply of a battery is available.

Art. 5025

Pompa elettrica per travaso battery kit 12V 50 l/min

Composta da:

- Art. 5080 Pompa 12V
- Art. 5404 Tubo racc. 4 m Ø 20 mm
- Art. 5200 Pistola alluminio "MC80"
- Art. 5256 Filtro di fondo + portagomma
- Art. 5270 Raccordo 3/4" + fascette

Transfer electric pump battery kit 12V 50 l/min

Composed by:

- 12V Pump
- Connected hose Ø 20 mm l. 4 m
- Aluminium hand-nozzle "MC80"
- Bottom-filter + hose connector
- 3/4" fitting + hose clamps

Art. 5026

Pompa elettrica per travaso battery kit 24V 50 l/min

Composto come Art. 5025 ma con:

- Art. 5082 Pompa 24 V

Transfer electric pump battery kit 24V 50 l/min

Composed like Mod. 5025 but with:

- Pump 24V

Art. 5030

Kit pompa elettrica per travaso da fusti 12V 50 l/min

Composto da:

- Art. 5080 Pompa 12V
- Art. 5404 Tubo racc. 4 m Ø 20 mm
- Art. 5200 Pistola alluminio "MC80"
- Art. 5280 Raccordo 3/4" - 2"
- Art. 5285 Pescante telescopico

Electric pump kit for transfer from drums 12V 50 l/min

Composed by:

- Pump 12V
- Connected hose Ø 20 mm l. 4 m
- Aluminium hand-nozzle "MC80"
- 3/4" - 2" quick coupling
- Telescopic shank

Art. 5032

Kit pompa elettrica per travaso da fusti 24V 50 l/min

Composto come Art. 5030 ma con:

- Art. 5082 Pompa 24 V

Electric pump kit for transfer from drums 24V 50 l/min

Composed like Mod. 5030 but with:

- Pump 24V



Articolo Model	Peso Weight	Mc Mc	Scatola Packing
5025	7,500	0,019	345x350x160
5026	7,500	0,019	345x350x160
5030	9,000	0,055	390x490x285
5032	9,000	0,055	390x490x285

Dati Tecnici Technical Data	Art.	5025	5026	5030	5032
Portata Flow rate	l/min	50	50	50	50
Tensione Tension	V	12	24	12	24
Giri motore R.P.M.	r.p.m.	2900	2900	2900	2900
Connessione entrata-uscita Inlet-outlet connection	G	F 3/4"	F 3/4"	F 3/4"	F 3/4"
Ciclo di lavoro Duty cycle	min	30	30	30	30

Sistema di travaso carburanti diesel ad uso privato. Consente un rifornimento degli automezzi sicuro e veloce, oltre alla misurazione e alla registrazione delle quantità erogate.

System for diesel fuel transferring for personal use. It allows the quick and safe filling of the vehicles, and also the options for measuring and recording the dispensed quantities.

Art. 5040

Kit pompa elettrica per travaso da fusti 230V 45 l/min "Tank Kit"

Composto da:

- Art. 5090 Pompa 230V
- Art. 5230 Contalitri meccanico
- Art. 5404 Tubo racc. 4 m Ø 20 mm
- Art. 5210 Pistola automatica "PA60"
- Art. 5282 Raccordo 1" - 2"
- Art. 5285 Pescante telescopico

Electric pump kit for transfer from drums 230V 45 l/min "Tank Kit"

Composed by:

- Pump 230V
- Mechanical flow meter
- Connected hose Ø 20 mm l. 4 m
- Automatic hand-nozzle "PA60"
- 1" - 2" quick coupling
- Telescopic shank



Art. 5045

Distributore travaso gasolio 230V 55 l/min "Compact 45"

Composto da:

- Art. 5090 Pompa elettrica 230V
- Art. 5230 Contalitri meccanico
- Art. 5404 Tubo racc. 4 m Ø 20 mm
- Art. 5210 Pistola automatica "PA60"

Dispenser for fuel transfer 230V 55 l/min "Compact 45"

Composed by:

- 230V electric pump
- Mechanical flow meter
- Connected hose Ø 20 mm l. 4 m
- Automatic nozzle "PA60"



Dati Tecnici Technical Data	Art.	5040	5045
Portata Flow rate	l/min	45	45
Tensione Tension	Volt/Hz	230/50	230/50
Giri motore R.P.M.	r.p.m.	2800	2800
Connessione entrata-uscita Inlet-outlet connection	G	F 1"	F 1"
Ciclo di lavoro Duty cycle	min	continuo	continuo

Articolo Model	Peso Weight	Mc Mc	Scatole Packing
5040	16,000	0,055	390x490x285
5045	17,000	0,055	390x490x285

Sistema di travaso carburanti diesel ad uso privato. Consente un rifornimento degli automezzi sicuro e veloce, oltre alla misurazione e alla registrazione delle quantità erogate.

System for diesel fuel transferring for personal use. It allows the quick and safe filling of the vehicles, and also the options for measuring and recording the dispensed quantities.



Art. 5050

Distributore travaso gasolio 230V 55 l/min "Compact 55"

Composto da:

- Art. 5095 Pompa 230V
- Art. 5230 Contalitri meccanico
- Art. 5405 Tubo racc. 4 m Ø 20 mm
- Art. 5210 Pistola automatica "PA60"

Dispenser for fuel transfer 230V 55 l/min "Compact 55"

Composed by:

- Pump 230V
- Mechanical flow meter
- Connected hose Ø 20 mm l. 4 m
- Automatic hand-nozzle "PA60"



Art. 5052

Distributore a colonna per travaso gasolio 230V 55 l/min "Dispenser 55"

Composto da:

- Art. 5095 Pompa elettrica 230V
- Art. 5230 Contalitri meccanico
- Art. 5405 Tubo racc. 4 m Ø 20 mm
- Art. 5210 Pistola automatica "PA60"

Dispenser with pedestal for fuel transfer 230V 55 l/min "Dispenser 55"

Composed by:

- 230V electric pump
- Mechanical flow meter
- Connected hose Ø 20 mm l. 4 m
- Automatic nozzle "PA60"



Articolo Model	Peso Weight	Mc Mc	Scatole Packing
5050	22,000	0,075	380x550x360
5052	45,000	0,192	380x1400x360

Dati Tecnici Technical Data	Art.	5050	5052
Portata Flow rate	l/min	55	55
Tensione Tension	Volt/Hz	230/50	230/50
Giri motore R.P.M.	r.p.m.	2800	2800
Connessione entrata-uscita Inlet-outlet connection	G	F 1"	F 1"
Ciclo di lavoro Duty cycle	min	continuo	continuo

Sistema di travaso carburanti diesel ad uso privato. Consente un rifornimento degli automezzi sicuro e veloce, oltre alla misurazione e alla registrazione delle quantità erogate.

System for diesel fuel transferring for personal use. It allows the quick and safe filling of the vehicles, and also the options for measuring and recording the dispensed quantities.

Art. 5060

Distributore travaso gasolio 230V 70 l/min "Compact 70"

Composto da:

- Art. 5098 Pompa 230V
- Art. 5230 Contalitri meccanico
- Art. 5424 Tubo racc. 4 m Ø 25 mm
- Art. 5210 Pistola automatica "PA60"

Dispenser for fuel transfer 230V 70 l/min "Compact 70"

Composed by:

- Pump 230V
- Mechanical flow meter
- Connected hose Ø 25 mm l. 4 m
- Automatic hand-nozzle "PA60"



Art. 5062

Distributore a colonna per travaso gasolio 230V 70 l/min "Dispenser 70"

Composto da:

- Art. 5098 Pompa elettrica 230V
- Art. 5230 Contalitri meccanico
- Art. 5424 Tubo racc. 4 m Ø 25 mm
- Art. 5210 Pistola automatica "PA60"

Dispenser with pedestal for fuel transfer 230V 70 l/min "Dispenser 70"

Composed by:

- 230V electric pump
- Mechanical flow meter
- Connected hose Ø 25 mm l. 4 m
- Automatic nozzle "PA60"



Dati Tecnici Technical Data	Art.	5060	5062
Portata Flow rate	l/min	70	70
Tensione Tension	Volt/Hz	230/50	230/50
Giri motore R.P.M.	r.p.m.	2800	2800
Connessione entrata-uscita Inlet-outlet connection	G	F 1"	F 1"
Ciclo di lavoro Duty cycle	min	continuo	continuo



Articolo Model	Peso Weight	Mc Mc	Scatola Packing
5060	25,000	0,075	380x550x360
5062	48,000	0,192	380x1400x360

Elettropompe di tipo rotativo a palette autoadescanti con tenuta meccanica che garantisce un'elevata affidabilità anche a basse temperature. Trovano impiego nell'equipaggiamento di distributori di gasolio e in impianti fissi di travaso.

Self-priming rotary vane electric pumps with a mechanical seal that guarantees constant reliability, even at low temperature. They can be used both for equipping fuel pumps and fuel transfer fixed installations.

Art. 5080

Pompa elettrica per travaso 12V 50 l/min

- Pompa rotativa a palette autoadescante
- Corpo in ghisa
- Valvola by-pass incorporata
- Motore a corrente continua
- Cavi di alimentazione 1.2 m + pinze
- Filtro in acciaio inox in aspirazione

Electric pump for transfer 12V 50 l/min

- Self-priming rotary electric pump
- Cast iron body
- In-built by-pass valve
- DC engine
- 2 mt cables + clips
- Inox filter



Art. 5082

Pompa elettrica per travaso 24V 50 l/min

Come Art. 5080 ma 24V

Electric pump for transfer 24V 50 l/min

Like Art. 5080 but 24V

Art. 5090

Pompa elettrica per travaso "LP3" 230V 45 l/min

- Pompa rotativa a palette autoadescante
- Corpo in ghisa
- Valvola by-pass incorporata
- Motore a corrente alternata
- Cavi di alimentazione 1.2 m + spina

Electric pump for transfer "LP3" 230V 45 l/min

- Self-priming rotary electric pump
- Cast iron body
- In-built by-pass valve
- AC engine
- 2 mt cables + Schuko plug



Art. 5095

Pompa elettrica per travaso "LP5" 230V 55 l/min

- Pompa rotativa a palette autoadescante
- Corpo in ghisa
- Valvola by-pass incorporata
- Motore a corrente alternata
- Cavi di alimentazione 1.2 m + spina
- Filtro 100 µ incorporato

Electric pump for transfer "LP5" 230V 55 l/min

- Self-priming rotary electric pump
- Cast iron body
- In-built by-pass valve
- AC engine
- 2 mt cables + Schuko plug
- In-built 100 µ filter



Art. 5098

Pompa elettrica per travaso "LP7" 230V 70 l/min

Come Art. 5095 ma con attacchi flangiati

Electric pump for transfer "LP7" 230V 70 l/min

Like Art. 5095 but with flanged joints



Articolo Model	Peso Weight	Mc Mc	Scatola Packing
5080	4,300	0,040	210x160x120
5082	4,300	0,040	210x160x120
5090	7,500	0,160	180x345x260
5095	7,900	0,190	195x355x270
5098	7,900	0,190	195x355x270

Dati Tecnici Technical Data	Art.	5080	5082	5090	5095	5098
Portata Flow rate	l/min	50	50	45	55	70
Tensione Tension	V	12	24	230/50	230/50	230/50
Watt Power watt	W	330	330	350	370	500
Giri motore R.P.M.	r.p.m.	2900	2900	2800	2800	2800
Connessione entrata-uscita Inlet-outlet connection	G	F 3/4"	F 3/4"	F 1"	F 1"	F 1" flanged
Ciclo di lavoro Duty cycle	min	30	30	Cont.	Cont.	Cont.